

# ACCESSORIES

The following accessories needed for installation are included for each gauge



- Gauge fluid 30 ml
- Fixing screws
- Stickers **FILTER CLEAN** and **FILTER DIRTY**
- Connection tube 1,5 m 4/6 PVC

## MM200600 MANOMETER INSTRUCTIONS

### INSTALLATION

Locate the manometer on a convenient vertical surface.  
Install gauge horizontally with self-drilling screws provided.

### FILLING

Gauge fluid is red coloured paraffine oil (density 0,786 kg/dm<sup>3</sup>, at 15°C).  
Back out the zero adjust knob until it stops: then turn in approximately one full turn so that there is room for adjustment in either direction.  
Remove the FILL plug and fill with gauge fluid until fluid is visible in vicinity of zero on scale.  
Adjust for exact setting with zero knob and replace FILL plug.

### FITTINGS WITH AIR FILTER

Run the tube from the fitting on the discharge side of the filter to the right gauge connection (-) and the tube from the other side of the filter to the left gauge connection (+). Remove paper from back of green and red stickers and install adjacent to the indicating tube to show clean and dirty filter readings.

### MAINTENANCE

Check oil level regularly and adjust zero knob as required. Be sure all pressure is removed by disconnecting tubing at top of gauge before adjusting zero knob. Add oil when necessary.

AEROFILTRI Srl  
Via Rubens, 23 - 20148 MILANO  
Tel.: 02 - 48705894  
Fax.: 02 - 48705893  
Email: [info@aerofiltri.it](mailto:info@aerofiltri.it)

