
Hi-Tech Silicone-free thread

Sewing threads normally contain silicon, used as slipper in the production process.








Performance Engineered Air Filter Products


made of selfextingushing paper*
*F1 - DIN 53438 Part 3

Performance engineered structure combines mechanical and baffle filtration to encourage depth loading.

The graphic is for explanation pourposes only and do not correspond to any standard type. Even if it might be produced if necessary




Uniform big diamond openings (27x18 mm) trap big drops yet allowing great air flow levels and encouraging depth loading rather than surface loading.



large openings (15x7 mm) keep on forcing changes in air direction, creating a turbulence very effective in capturing paint particles.

Here is where mid-size drops find their final settlement.



9x4 mm mesh retains very small droplets. It was known as the smallest mesh before the appearance of the mini-mesh technology.

1 "mini-mesh"

layer

4x2.5 mm opening is the outcome of an unparalleled technology. Mini-mesh gives the extra efficiency needed to comply with today's restrictive emission norms.

AEROFILTRI.

VISIT US AT HALL 25

Via Rubens, 23 • 20148 Milano • Italy
Tel. +39 02 48 70 58 94 • TeleFAX +39 02 48 70 58 93
info@aerofiltri.it • www.aerofiltri.it

1 Polyester final layer

A vast choice of optional polyesterfiber final layers allows to adjust efficiency to real needs.



Glass Fiber Paint Stop



BOOTH C-57

Polyester preFilters G2-G4



Ceiling Filters F5



Inertia
Pleated Filters



Panel Filters



Mini-Pleat F5-H10



Bag Filters G2-F9



Plastic Frame Bag Filters F5-F9



Manometers and Pressure Switches



Pressure Gauges



Multipoint Pitot Tubes



High Volume Smoke Generators